

Terrace systems » Tilt and slide PSK » IGLO5 PSK



Tilt and slide balcony door PSK Iglo 5

Perfect solution that ensures big access to daylight both in small and big room, maintaining great thermal insulation at the same time.

Features

- 1. Design that reflects innovativeness and unconventionality.
- 2. High safety level guaranteed by the application of four anti-burglary bolts in standard.
- Possibility to customize the interior as the result of the wide range of colours;
- Very good thermal parameters ensure heat saving thanks to optimal structure and EPDM sealing.
- 5. Good parameters in sound insulation that guarantee acoustic comfort.
- 6. The possibility to execute in the so-called thin wielding technology (V-Perfect), that allows to connect the profiles perfectly and it guarantees better clamp and wielding control, and, as a result, very good parameters in the resistance tests of the corners (Iglo 5 Classic).

Technical data

Fittings The possibility to apply automatic fitting that supports tilt closing. Four anti-burglary bolts in standard.

Sound isolation -

One-chamber glass package with thermal transmittance Ug=1,0 $W/(m^2K) \ according \ to \ the \ PN-EN674 \ norm \ in \ standard. \ The \ possibility \ to \ apply \ Glass \ three-glass \ package \ with \ Ug = 0,6 \ W/(m^2K). \ Maximal \ glazing \ thickness \ up \ to \ 40 \ mm. \ The \ possibility \ to \ apply \ glasses \ with \ enhanced \ sound \ insulation, \ tempered,$

safety, anti-burglary, ornament or solar protective.

Colour range The system is available in Renolit foil colours on white or brown core.

Profile 5-chamber frame and sash profiles made exclusively of prime material in A-class with installation width 70 mm.

Reinforcement Frame reinforcement – full steel (closed). In the full reinforcement, anti-burglary bolts are screwed to the steel. C-shaped reinforcement beam in the sash.

The door is equipped with a system of double sealing; external, internal made

Gaskets of EPDM, available in black, grey colours. Gasket that fullfills the bottom fitting

ditch in standard.

Spacer frame Steel galvanized spacer frame in standard. Optionally Swisspacer Ultimate available in various colour options.